



<b>LED/Multiled :</b>	<i>LED</i>	<b>Optimum voltage (V) :</b>	<i>110VAC</i>	<b>Intensity :</b>	<i>250mcd@20mA</i>
<b>Mounting Size :</b>	<i>8mm</i>	<b>Rectifier :</b>	<i>-</i>		
<b>Bezel Finish :</b>	<i>Bright Chrome</i>	<b>AC current :</b>	<i>6mA</i>		
<b>Sealing Protection :</b>	<i>IP67</i>	<b>DC current :</b>			
<b>Bezel Style :</b>	<i>Flush</i>	<b>Voltage Tolerance(%) :</b>	<i>10%</i>		
<b>Chip Qty :</b>	<i>1</i>	<b>Optimum temperature (°C) :</b>	<i>-40°C...+85°C</i>	<b>Principal Attributes</b>	
<b>LED colour :</b>	<i>Yellow</i>	<b>Storage temperature (°C) :</b>	<i>-40°C...+85°C</i>		
<b>Wavelength (nm) :</b>	<i>589</i>	<b>Contact Tab x 2 :</b>	<i>2.8x0.8mm</i>		



*Dimension in mm (typical), not to scale.  
We reserve the right to make changes without further notice to this product to improve reliability, function or design.*