




.040 MULTILOCK Connectors (Mark II)

Wire to Wire Applications

Tab Contact (To be used with cap housing for wire to wire connections.)

Contact	Wire Range	Wire Ins. Diameter	Material/Finish	Part No.		Hand Tool No. (Instruction Sheet)
				S.T.	L.P.	
.040 Tab  Crimp Specifications: 114-5108	0.3~0.5mm ² (AWG#22-20)	∅1.8-2.0mm	Brass/Pre-tin	173682-1	175063-1	91577-1 (411-5417)

Receptacle Contact (To be used with plug housing.)

Contact	Wire Range	Wire Ins. Diameter	Material/Finish	Part No.		Hand Tool No. (Instruction Sheet)
				S.T.	L.P.	
.040 Receptacle  Crimp Specifications: 114-5094	0.3~0.5mm ² (AWG#22-20)	∅1.8-2.0mm	Copper Alloy/Pre-tin	173681-1	175062-1	91577-1 (411-5417)
			Copper Alloy/Sel. Gold	173681-2	175062-2	
.040 Receptacle  For an extra-thin jacketed cable Crimp Specifications: 114-5162	0.3~0.5mm ² (AWG#22-20)	∅1.1-1.6mm	Copper Alloy/Pre-tin	175180-1	—	—
			Copper Alloy/Sel. Gold	175180-2	—	



Cap (To be used with .040 tab contact.)

Plug (To be used with .040 rec. contact.)

Part Number : 1123882-2

12
Pos.

Part Number : 175965-2



*The material of housing is of PBT, and its color is black.
 *16 pos. is available. (cap P/N : 1473196-1, Plug P/N : 175966-2)