



SNK Terminal Blocks T&B Catalog Number:

1SNK506310R0000

UPC Number:

80432548891

Status:

Active

Description:

Gray terminal block disconnect with blade with 6 mm spacing, 26 amp UL rated current with screw clamp connection

Features

Ease your disconnect operations with the disconnect blade operated by hand or with a screwdriver
Same profile as ZS4 feed-through terminal blocks for aligned marking and identical end section use

Application

For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc.

General

Style	Disconnect with Blade
Color	Gray
Mounting	DIN 3
Series	ZS4-S-R1
Connection Technology	Screw Clamp
UL Wire Range (AWG)	24-10
Rated IEC Wire Range (Solid) (mm ²)	0.2-4
Rated IEC Wire Range (Stranded) (mm ²)	0.22-4

Dimension Information

L x W x H (mm)	70.5 x 6 x 59.7
Spacing (mm)	6
L x W x H (in)	2.78 x .236 x 2.35
Spacing (inches)	0.236

Specifications

UL Current (Amps)	26
UL Voltage (VAC)	150

Packaging

T&B Order Multiple	50
T&B Inner Pack	50
Package in Units	600
T&B Sold in UOM	Each
T&B Weight Per UOM	0.03 lbs. Each

Certifications

Approvals	USR, CSA, CE
-----------	--------------

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com