

Data sheet

2 way PCB terminal block 5.0mm

Type No. : MB612-500
Order No. : MB612-500xx

RoHS
Compliant

PCB Layout

Pitch : 5.00mm(0.197inch)					
Poles	A(mm)	B(mm)	Poles	A(mm)	B(mm)
2	10.00	5.00	15	75.00	70.00
3	15.00	10.00	16	80.00	75.00
4	20.00	15.00	17		
5	25.00	20.00	18		
6	30.00	25.00	19		
7	35.00	30.00	20		
8	40.00	35.00	21		
9	45.00	40.00	22		
10	50.00	45.00	23		
11	55.00	50.00	24		
12	60.00	55.00	25		
13	65.00	60.00			
14	70.00	65.00			

Current rating : 16Amp AC300V
 Insulation withstands volt : AC2000V min
 Insulation resistance : >2000MΩ DC500V
 Operation temperature : -40°C to +105°C
 Wire strip length : 4mm~5mm
 Wire range : 14~26 AWG
 Screw torque : 4.5 lb-inch

CONFIRMED & ACCEPTED BY _____

文件管制
MAR 19, 2012
文管中心

	Material	Plating/Finish	Remark
1	Insulating body Polyamide 66(UL94V-0)		Green
2	Terminal Brass	Tin plated	
3	Screw Steel	Zinc plated	
4	Cage clamp Brass	Ni plated	

Order No. MB612-500xx

SHEET OF 2/2

METRIC MM

DRAWN BY *Sy*

DATE 2012/03/19

VERSION D

CONFIRMED BY *Wenderson*

GENERAL MANAGER *Jallex*

單據編號 : QR-0703-08 版次 :A版

