

RAISED COVER WITH SCREWS, TYPE 4X

INDUSTRY STANDARDS

UL 508A Listed; Type 3, 3R, 4, 4X, 12, 13; File No. E54315
 cUL Listed per CSA C22.2 No 94; Type 3, 3R, 4, 4X, 12, 13; File No. E54315
 Enclosure flammability per UL 508A

NEMA/EEMAC Type 3, 3R, 4, 4X, 12, 13
 CSA File No. 217184: Type 3, 3R, 4, 4X, 12, 13
 IEC 60529, IP66
 Meets NEMA Type 3RX requirements

APPLICATION

Enclosures feature a raised, overlapping-cover design that ensures a more-secure seal and offers increased internal space for mounting components. Available with removable and hinged covers for application flexibility.

SPECIFICATIONS

- Compression-molded fiberglass construction
- Overlapping solid raised-cover
- Cover fastens with screws
- Type 304 stainless steel piano hinges on hinged models
- Integral mounting brackets
- Enclosures protect equipment and operators from indirect electrical contact

FINISH

Fiberglass material is RAL 7035 light-gray inside and out. Optional steel panels are painted white. Optional stainless steel, aluminum, conductive and composite panels are unpainted.

ACCESSORIES

See also Accessories.
 H2OMIT™ Vent Drains, Type 4X
 HOL-SEALERS™ Non-Metallic Hole Seals
 Panels for Junction Boxes
 Swing-Out Panel Kit
 Terminal Block Kit Assembly for Junction Boxes Overview

MODIFICATION AND CUSTOMIZATION

Hoffman excels at modifying and customizing products to your specifications. Contact your local Hoffman sales office or distributor for complete information.

BULLETIN: HJ

Standard Product

Catalog Number	AxBxC in./mm	Door Fasteners	D in./mm	F in./mm	G in./mm	H in./mm	I in./mm	J in./mm	K in./mm	L in./mm	P in./mm	Q in./mm	W in./mm	Steel Panel	Alum Panel	Panel Size in./mm
RHJ1008HWLG	9.70 x 7.71 x 5.91	Hinged,	6.86	6.49	10.75	6.00	11.51	4.50	3.15	11.22	8.25	6.25	9.22	A10P8	A10P8AL	8.75 x 6.88
	246 x 196 x 150	2 screws	174	165	273	152	292	114	80	285	210	159	234			222 x 102
RHJ1008WLG	9.70 x 7.71 x 5.91	4 screws	6.86	6.49	10.75	6.00	11.51	4.50	3.15	11.22	8.25	6.25	9.22	A10P8	A10P8AL	8.75 x 6.88
	246 x 196 x 150		174	165	273	152	292	114	80	285	210	159	234			222 x 102
RHJ1210HWLG	11.68 x 9.69 x 6.16	Hinged,	7.05	6.73	12.75	6.00	13.51	4.66	3.15	13.22	10.25	8.25	11.22	A12P10	A12P10AL	10.75 x 8.88
	296 x 246 x 156	2 screws	179	171	324	152	343	118	80	336	260	210	285			273 x 226
RHJ1210WLG	11.68 x 9.69 x 6.16	4 screws	7.05	6.73	12.75	6.00	13.51	4.66	3.15	13.22	10.25	8.25	11.22	A12P10	A12P10AL	10.75 x 8.88
	296 x 246 x 156		179	171	324	152	343	118	80	338	260	210	285			273 x 226
RHJ1412HWLG	13.62 x 11.62 x 7.24	Hinged,	8.13	7.81	14.75	10.00	15.51	5.63	3.25	15.22	12.25	10.25	13.22	A14P12	A14P12AL	12.75 x 10.88
	346 x 295 x 184	2 screws	207	194	375	254	394	143	82	387	311	260	336			324 x 276
RHJ1412WLG	13.62 x 11.62 x 7.24	4 screws	8.13	7.81	14.75	10.00	15.51	5.63	3.25	15.22	12.25	10.25	13.22	A14P12	A14P12AL	12.75 x 10.88
	346 x 295 x 184		207	194	375	254	394	143	82	387	311	260	336			324 x 276
RHJ1614HWLG	15.62 x 13.62 x 7.24	Hinged,	8.13	7.81	16.75	12.00	17.51	5.63	3.25	17.22	14.25	12.25	15.22	A16P14	A16P14AL	14.75 x 12.88
	396 x 346 x 184	2 screws	207	194	425	305	445	143	82	437	362	311	386			375 x 327
RHJ1614WLG	15.62 x 13.62 x 7.24	4 screws	8.13	7.81	16.75	12.00	17.51	5.63	3.25	17.22	14.25	12.24	15.30	A16P14	A16P14AL	14.75 x 12.88
	396 x 346 x 184		207	194	425	305	445	143	82	437	362	311	289			375 x 327
RHJ1816HWLG	17.48 x 15.77 x 9.44	Hinged,	10.25	10.01	18.75	12.00	19.51	7.76	3.25	19.22	16.25	14.25	17.22	A18P16	A18P16AL	16.75 x 14.88
	444 x 400 x 240	2 screws	260	254	476	305	496	197	82	488	413	362	437			425 x 378
RHJ1816WLG	17.48 x 15.77 x 9.44	4 screws	10.25	10.01	18.75	12.00	19.51	7.76	3.25	19.22	16.25	14.25	17.22	A18P16	A18P16AL	16.75 x 14.88
	444 x 400 x 240		260	254	476	305	496	197	82	488	413	362	437			425 x 378

A x B x C are internal dimensions.

Purchase panels separately. Optional stainless steel, composite and aluminum panels are available for most sizes.

