



- NOTES:
1. MATERIAL: NYLON 6,6
 2. FLAMMABILITY RATING: UL94V-2
 3. MAXIMUM OPERATING TEMP: 185F(85C)
 4. MINIMUM TENSILE RATING: 18 LBS (80 N)
 5. MINIMUM BUNDLE DIA: 0.0625 [1,59]
 6. MAXIMUM BUNDLE DIA: 0.75 [19,0]
 7. Part Number B4M* ** (MS3367-4-*)
 8. UL 62275 Type 2/21
 9. Min. Installation Temp. 0C (32F)

* = NUMBER/COLOR	0 - Black	6 - Blue	12 - Florescent Pink
	1 - Brown	7 - Purple	13 - Florescent Yellow
	2 - Red	8 - Gray	14 - Florescent Orange
	3 - Orange	9 - Natural	15 - Florescent Blue
	4 - Yellow	10 - White	HS - Heat Stabilized
	5 - Green	11 - Florescent Green	AH - Air Handling (NEC 300-22 (c) and (D))

** = PACKAGE M = 1,000 D = 500 H = 250 C = 100 L = 50 Q = 25				Quest Technology Int'l, Inc. 11200 NW 138th St., Medley, FL 33178 Tel: 305-513-8883 Fax: 305-513-9676 www.questtechnologyintl.com	
	Miniature (Min) Cable Tie 18 LB (80) Series				
ALL DIMENSIONS ARE FOR REFERENCE ONLY UNLESS SPECIFIED ALL DIMENSIONS ARE IN INCHES AND MILLIMETERS [0,0]	SIZE A	FSCM NO.	DWG NO. NWT-804X	REV 2	
	SCALE N/A	Material Nylon 6/6	SHEET 1 of 1		