



HARTING
Katalog-Informationen-System
Version 11.0



[Home page](#)

- [Applications](#)
 - [EDP](#)
 - [Telecommunication](#)
 - [FTTA \(Fibre To The Antenna\)](#)
 - [Professional electronics](#)
 - [Automation technology](#)
 - [Mechanical Engineering](#)
 - [Transportation](#)
- [Products](#)
 - [Industrial Connectors Han®](#)
 - [Devices and Components](#)
 - [Front Panel Interfaces](#)
 - [Circular Connectors](#)
 - [Ethernet Components](#)
 - [Ethernet Cabling](#)
 - [Connectors for TCA](#)
 - [har-bus® HM](#)
 - [har-bus® HM 6-row](#)
 - [har-bus® HM Power](#)
 - [Mini Coax](#)
 - [har-link®](#)
 - [har-pak®](#)
 - [DIN 41 612](#)

- [PushPull Power](#)
- [Flat Cable Connectors SEK](#)
- [har-mik®](#)
- [D-Sub](#)
- [InduCom](#)
- [Help](#)
 - [HARKIS® help](#)

Search by

- [Industrial Connectors and Equipment](#)
 - [Industrial Connectors Han®](#)
 - [Devices and Components for Automation](#)
 - [Front Panel Interfaces](#)
 - [Circular Connectors](#)
- [Ethernet](#)
 - [Ethernet Components](#)
 - [Ethernet Cabling](#)
- [Metric Connectors](#)
 - [Connectors for TCA](#)
 - [har-bus® HM](#)
 - [har-bus® HM 6-row](#)
 - [har-bus® HM Power](#)
 - [Mini Coax](#)
 - [har-link®](#)
 - [har-pak®](#)
- [DIN Connectors](#)
 - [DIN 41 612](#)
- [I/O Connectors and Equipment](#)
 - [PushPull Power](#)
 - [Flat Cable Connectors SEK](#)
 - [har-mik®](#)
 - [D-Sub](#)
 - [InduCom](#)
- [Applications](#)

Product details

[Back](#)

09 45 771 0127

Cable assembly for Industrial Ethernet

Cable type	Cable assembly for Industrial Ethernet
Connectors	1x HARTING RJ Industrial® IP 20 Data with overmoulded housings
Type of cable	Stranded cable AWG 22/7
Transmission characteristics	in accordance with ISO/IEC 11801:2002: Class D
Length	5.0 m
Protection level	IP 20 (when mated)
Sheath	PVC green, ? mm
Mating interface	RJ 45 acc. to IEC 60 603-7
RoHS compliant ex warehouse	Yes

Available Downloads

Title	Format
CAD data 3D IGES	download
CAD data 3D STEP	download
CAD data 3D VRML	download

Product news



Han® RJ45 Module

This shielded Ethernet Module connects all 8 datalines and fulfils the cat 5e requirements.

[More information](#)

[Imprint](#)

[Go to top](#)

© HARTING KGaA Marienwerderstr. 3 32339 Espelkamp Tel. 05772 - 470 Fax. 05772 - 47 400