

9001KR9GM95

green non-illum pushbutton op type K Ø30 -maint-push/pull metal mush-w/o contact



[Download your 9001KR9GM95 datasheet](#)

[Characteristics](#) | [Dimensions Drawings](#) | [Mounting and Clearance](#) | [Documents & Downloads](#)

Main

[Hide](#)

Range of product	Harmony 9001K
Product or component type	Complete non-illuminated mushroom head pushbutton
Product compatibility	Contact block 9001KA..
Device short name	9001K
Type of operator	Push-pull
Operator profile	Green mushroom Ø 60 mm unmarked

Complementary

[Hide](#)

Bezel material	Chromium plated metal
Mounting diameter	30 mm
CAD overall width	60 mm
CAD overall height	60 mm
CAD overall depth	70...74 mm
Product weight	0.15 kg
Operating position	Any position
Shape of signaling unit head	Round
Head material	Metal
Operator additional information	Screw-in with set screw security
Operator position information	2 positions
Contacts type and composition	Without contact block
Mechanical durability	5000000 cycles

Environment

[Hide](#)

Protective treatment	TC
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-25...70 °C
Class of protection against electric shock	Class II conforming to IEC 61140
IP degree of protection	IP66 conforming to IEC 60529
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3R NEMA 4 NEMA 6
Standards	EN/IEC 60947-5-1 EN/IEC 60947-1

EN/IEC 60947-5-4
JIS C 4520
JIS C 852
UL 508
CSA C22.2 No 14

Product certifications

NEMA
UL 508

Vibration resistance

7 gn (f = 2...500 Hz) conforming to IEC 60068-2-6

Shock resistance

50 gn conforming to IEC 60068-2-27

**Contractual
warranty**

 **Hide**

Period

18 months