


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	8/14/12	D.GRIFFIN



LENGTH CODE CHART		
CABLE# & LENGTH	LENGTH SYMBOL	EXAMPLES OF PART# USED
CA-RSPRSJAXXX	WHERE XXX = LENGTH IN FEET	CA-RSPRSJA010 (10 FEET)
CA-RSPRSJANXX	WHERE NXX = LENGTH IN INCHES	CA-RSPRSJAN16 (16 INCHES)
CA-RSPRSJAMXX	WHERE MXX = LENGTH IN METERS	CA-RSPRSJAM07 (7 METERS)
CA-RSPRSJAXMX	WHERE XMX = LENGTH IN DECIMAL METERS	CA-RSPRSJA3M5 (3.5 METERS)

**RoHS Compliant** ✓

NOTES:

1. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
2. CABLE ASSEMBLY SHALL RECEIVE INSERTION LOSS TEST PER L-COM SPECIFICATIONS.
3. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +3% / -0%	APPROVALS	DATE		45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845
	DRAWN BY D.FRISIELLO	8/13/12		CATEGORY
ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 .XX = ±.02 .XXX = ±.005	CHECKED BY T. VADEN	8/13/12	PRODUCT DESCRIPTION	
PROJECTION 	APPROVED BY P.PESA	8/13/12	CA, 195R RSP - RSJ	
CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY	COLOR VARIATIONS MAY OCCUR	SIZE <b>A</b>	FSCM NO. <b>43321</b>	DWG. NO. CA-RSPRSJA
SCALE: NONE		CAD FILE: CA-RSPRSJA.SLDDRW		REV. <b>A</b>
				SHEET 1 OF 1