

OUTPUT INTERFACE WITH PLUG-IN RELAY, 1 NO CONTACT
SCREW TERMINAL 24 V DC ENCLOSURE WIDTH 6.2 MM



General technical data:

Type of voltage	DC
Control supply voltage	
<ul style="list-style-type: none"> • at DC Rated value <ul style="list-style-type: none"> — minimum 24 V — maximum 24 V 	
Switching behavior	monostable
Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	1
Number of CO contacts for auxiliary contacts	0
Operating current of the auxiliary contacts	
<ul style="list-style-type: none"> • at DC-13 <ul style="list-style-type: none"> — at 24 V 1 A — at 110 V 0.2 A — at 230 V 0.1 A • at AC-15 <ul style="list-style-type: none"> — at 230 V 3 A 	
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K

Equipment marking acc. to DIN EN 61346-2	K
--	---





Mechanical data:

Type of electrical connection	screw-type terminals
Type of electrical connection Plug-in socket	Yes
Design of the relay operating mechanism	poled
Design of the switching function positively driven	No
Product component Plug-in socket	Yes
Width	6.2 mm
Height	89.5 mm
Depth	92 mm

Ambient conditions:

Protection class IP	IP20
Ambient temperature during operation	-25 ... +55 °C

Certificates/ approvals:

General Product Approval	Declaration of Conformity	Test Certificates	other
 CCC	 UL		 EG-Konf.
		spezielle Prüfbescheinigunge n	Bestätigungen

Further information

- Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/industrial-controls/catalogs>
- Industry Mall (Online ordering system)
<http://www.siemens.com/industrymall>
- Cax online generator
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX70141AM00>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3TX70141AM00>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX70141AM00&lang=en

last modified: 17.07.2015