

**Olympic Wire and Cable**

7 Madison Road • Fairfield, NJ 07004

973.227.7996 800.526.2269 • Fax: 973.227.1606

email: sales@olympicwire.com

**Olympic P/N 363, UL LISTED UL1015, UL1032, UL1230****UL LISTED UL1015, UL1032, UL1230**


Stranded Tinned Copper, Color Coded PVC Insulation.

**Characteristics:**

Temperature Rating — 40°C to +105°C

Resistant to acids, alkalis, oil, flame, moisture and fungus

**SPECIFICATIONS**

|                       |  |
|-----------------------|--|
| Conductor Size        | 18 AWG   |
| Stranding             | 16/30 Tinned Copper  |
| Insulation            | PVC  |
| Nom. Wall Thickness   | 0.031 in   |
| Nom. O.D.             | 0.112 in   |
| UL Style              | 1015<br>1032<br>1230<br>MTW  |
| UL Rating             | 600 V, 90°C, 1000 V  |
| UL Flame Test         | VW-1   |
| CSA Type              | TEW, TR-32   |
| CSA Flame Test        | FT-1   |
| Operating Temperature | -40 to +105 °C   |
| RoHS Compliant        | <br>RoHS Compliant |
| Color Code            | Hook Up Wire Color Code Chart  |