

**VS-08-LI-VSIP67-VSIP67-CF-5,0**

Order No.: 1689572



Assembled Ethernet cable, CAT5e, shielded, 2-pair, AWG 26 stranded (7-wire), line, RAL 5021 (water blue), RJ45/IP67 on RJ45/IP67, length: 5 m

**Ethernet**

Commercial data	
EAN	4017918907518
Pack	1 Pcs.
Customs tariff	85369010
Weight/Piece	0.2426 KG
Catalog page information	Page 172 (PC-2007)

## Product notes

WEEE/RoHS-compliant since:  
08/08/2006



Technical data	
<b>Mechanical characteristics</b>	
Number of positions	4
Shielded	Yes
Insertion/withdrawal cycles	≥ 750
Cable diameter	5.80 mm

Cable structure	2x2xAWG26/7; SF/UTP
Smallest bending radius, fixed installation	30 mm
Smallest bending radius, movable installation	78 mm
Length of cable	5 m
Ambient temperature (operation)	-30 °C ... 80 °C (cable, fixed installation)
	-5 °C ... 60 °C (cable, flexible installation)
	(plug/socket)

**Material data**

Housing material	PA
Contact carrier material	Thermoplastic
Contact material	Copper alloy
Contact surface material	Gold over nickel
Material, O-ring	FPM
Cable seal material	NBR
Outer sheath, material	Halogen-free compound, HM 2 in acc. with VDE 0207
External sheath, color	water blue RAL 5021
Degree of protection	IP67

**Electrical characteristics**

Rated voltage (III/3)	60 V
Transmission characteristics (category)	CAT5 (IEC 11801:2002), CAT5e (TIA 568B:2001)

**Accessories**

Item	Designation	Description
<b>Protective covers</b>		
1653757	VS-SCRJ-PC	IP67 protective cover, for covering the male inserts in the sleeve housings IP67, VS-SCRJ-..., VS-04-..., VS-06-... and VS-08-...