



RECTANGULAR POWER CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE) FEMALE BLOCK 20 POS AMP | PKS

200346-2
TE Internal Number: 200346-2

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Receptacle**

Connector System **Cable-to-Cable, Cable-to-Panel**

Applies To **Panel, Wire/Cable**

Number of Positions **20**

Product Drawings

[BLOCK, FEMALE, 20 PLACE MINIATURE RECTANGULAR, M SERIES](#)
PDF (TIFF AVAILABLE)
English

[BLOCK, FEMALE, 20 PLACE MINIATURE RECTANGULAR, M SERIES](#)
PDF (TIFF AVAILABLE)
English

CAD Files

[Customer View Model](#)
2D_DXF.ZIP
English

[Customer View Model](#)
3D_IGS.ZIP
English

[Customer View Model](#)
3D_STP.ZIP
English

[3D PDF](#)
PDF
English

Catalog Pages/Data Sheets

[M_SERIES_PIN_AND_SOCKET_CONNECTORS](#)
PDF
English

Product Specifications

Product Specification [Subminiature COAXICON Contacts](#)
PDF
English

Product Environmental Compliance

TE Material Declaration [MD_200346-2_09242015126_dmtec](#)
PDF
English

Instruction Sheets

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type

Housing

Housing Type

Receptacle

Contact Type

Socket

Configuration Features

Number of Positions

20

Centerline

3.3 mm [.129 in]

Mechanical Attachment

Panel Mount Retention Type

Screw Mount

Panel Mount Retention

With

Housing Features

UL Flammability Rating

UL 94V-0

Housing Color

Black

Housing Material

Phenolic GF

Dimensions

Width

11.18 mm [.44 in]

Height

39.62 mm [1.56 in]

Length

23.24 mm [.915 in]

Usage Conditions

Sealed Condition

Not Sealed

Operation/Application

Connector System

Cable-to-Cable, Cable-to-Panel

Applies To

Panel, Wire/Cable

Operating Temperature

-55 – 150 °C [-67 – 302 °F]

Packaging Features

Packaging Method

Carton

Packaging Quantity










203

Other

For Use With

Pin Housing

CUSTOMERS ALSO BOUGHT

RECTANGULAR POWER CONNECTORS	PUSHBUTTON SWITCHES	RACK & PANEL CONTACTS	POWER CONTACTS
 <p>20 POS. MALE 201356-1</p>	<p>MPA106F=SWITCH P/B MOM SPDT MPA106F</p>	<p>PIN CONT, XZ 20, NIC 600 208265-3</p>	<p>062 SOC.ASS. TYP3+ 163088-1</p>
<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>