




## 928924-1 Product Details


**928924-1**

TE Internal Number: 928924-1

**Active**

### Timer Contacts

Always EU RoHS/ELV Compliant (Statement of Compliance)

#### Product Highlights:

- Timer Products Product Line
- Junior Timer Series, Junior-Power-Timer (JPT) Series, Multiple Circuit Housings with Tabs & Receptacles (Including FASTIN-FASTON) Series
- Wire-to-Wire
- Applies To Wire/Cable
- Contact

[View all Features](#)

### Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

### Documentation & Additional Information

Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.

#### Additional Information:

- [Product Line Information](#)

#### Additional Product Images:

- [Line Drawing](#)

#### Related Products:

- [Tooling](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Product Line = Timer Products
- **Product Type** = Contact
- Cable Type = FLR (Thin Walled Cable) - RB
- Wire/Cable Type = Discrete Wire
- Insulation Support = With

#### Electrical Characteristics:

- Contact - Rated Current (A) = 25

#### Termination Features:

- Wire/Cable Size (AWG) = 12 - 15
- Wire/Cable Size (mm<sup>2</sup>) = 1.5 - 3
- Termination Method to Wire/Cable = Crimp

#### Dimensions:

- Mating Area Interface Dimensions (mm [in]) = 2.79 x 0.79 [.110 x .031]

#### Contact Features:

- Contact Type = Tab
- Contact Design = FASTIN-FASTON
- Contact Base Material = CuZn30
- Contact Plating, Mating Area, Material = Pre-Tin
- Contact Plating, Mating Area, Thickness (µm [µin]) = 1 [39.37]

#### Configuration Features:

- GET 0.64 Connector System = No
- Single Wire Sealing System = No

#### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

#### Environmental:

- Operating Temperature (°C [°F]) = -40 - +130 [-40 - +266]

#### Conditions for Usage:

- Applies To = Wire/Cable
- Accepts Wire Insulation Diameter, Range (mm [in]) = 2.30 - 3.50 [0.090 - 0.1377]

#### Operation/Application:

- Application Use = Wire-to-Wire
- Contact Transmits (Typical Application) = Power

#### Packaging Features:

- Packaging Method = Loose Piece
- Packaging Quantity = 500

#### Other:

- Series = Junior Timer, Junior-Power-Timer (JPT), Multiple Circuit Housings with Tabs & Receptacles (Including FASTIN-FASTON)
- Brand = AMP

### Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

### Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

### Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

### Keep Me Informed



