*Product datasheet*
*Characteristics*

# XXZPB100

teach mode pushbutton - selection of detection window - for ultrasonic sensor

## Main

| | |
|---|---|
| Accessory / separate part designation | Teach mode pushbutton |
| Accessory / separate part destination | Ultrasonic sensor |
| Accessory / separate part category | Sensor accessories |
| Accessory / separate part type | Pushbutton |

## Complementary

| | |
|---|---|
| Product compatibility | XX518A3.AM12<br>XX7V1A1.AM12 |
| Electrical connection | 1 male connector M12 3 pins straight<br>1 female connector 4 pins straight |
| Product weight | 0.035 kg |

## Environment

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| RoHS | Compliant - since 1140 - Schneider Electric declaration of conformity |
| REACh | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Available |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.