

T&B Conduit Fittings Non-Metallic Cable Glands



Sturdy Nylon 6 for strong, lightweight construction. Gray color shown, also available in black.

Low profile cable gland perfect for tight spots

T&B Nylon Cable Glands have a sturdy cable sealing mechanism which results in superior strain relief. The compact size ensures quick and easy installation in cramped spaces. The non-metallic construction provides excellent corrosion, chemical and impact resistance. The glands have long threads and locknuts are available.



- Halogen free
- Flame Retardant UL 94V0
- Suitable for NEMA type 4X and type 6; IP 68 5 BAR
- UL Listed, CSA listed for certain ranges of cable
- Working Temperatures -30°C(-86°F) to +80°C(176°F) Continuous, +150°C(276°F) Intermittent

Non-Metallic Cable Glands

Catalog No. Fittings	Hub Size	Color	Cord Range		Length of Thread		Overall Length		Unit Pkg.	Std. Pkg.	UPC No. Fittings
			In.	MM	In.	MM	In.	MM			
NPT Threads											
CC-NPT-38-B	3/8"	BLACK	.197-.394	5-10mm	.590	15mm	.866	22mm	50	500	786210-95582
CC-NPT-38-G	3/8"	GRAY	.197-.394	5-10mm	.590	15mm	.866	22mm	50	500	786210-07817
CC-NPT-12-B	1/2"	BLACK	.394-.591	10-14mm	.590	15mm	1.063	27mm	50	500	786210-95583
CC-NPT-12-G	1/2"	GRAY	.394-.591	10-14mm	.590	15mm	1.063	27mm	50	500	786210-07824
CC-NPT-34-B	3/4"	BLACK	.511-.709	13-18mm	.590	15mm	1.299	33mm	25	100	786210-95584
CC-NPT-34-G	3/4"	GRAY	.511-.709	13-18mm	.590	15mm	1.299	33mm	25	100	786210-07853
CC-NPT-1-B	1"	BLACK	.709-.984	18-25mm	.709	18mm	1.654	42mm	20	100	786210-95586
CC-NPT-1-G	1"	GRAY	.709-.984	18-25mm	.709	18mm	1.654	42mm	20	100	786210-07854
ISO/Metric Threads											
CC-ISO-38-B	3/8"	BLACK	.197-.394	5-10mm	.590	15mm	.866	22mm	50	500	786210-99929
CC-ISO-38-G	3/8"	GRAY	.197-.394	5-10mm	.590	15mm	.866	22mm	50	500	786210-99933
CC-ISO-12-B	1/2"	BLACK	.394-.591	10-14mm	.590	15mm	1.063	27mm	50	500	786210-99930
CC-ISO-12-G	1/2"	GRAY	.394-.591	10-14mm	.590	15mm	1.063	27mm	50	500	786210-99934
CC-ISO-34-B	3/4"	BLACK	.511-.709	13-18mm	.590	15mm	1.299	33mm	25	100	786210-99931
CC-ISO-34-G	3/4"	GRAY	.511-.709	13-18mm	.590	15mm	1.299	33mm	25	100	786210-99935
CC-ISO-1-B	1"	BLACK	.709-.984	18-25mm	.709	18mm	1.654	42mm	20	100	786210-99932
CC-ISO-1-G	1"	GRAY	.709-.984	18-25mm	.709	18mm	1.654	42mm	20	100	786210-99936
PG Threads											
CC-PG-38-B	3/8"	BLACK	.197-.394	5-10mm	.590	15mm	.866	22mm	50	500	786210-99921
CC-PG-38-G	3/8"	GRAY	.197-.394	5-10mm	.590	15mm	.866	22mm	50	500	786210-99925
CC-PG-12-B	1/2"	BLACK	.394-.591	10-14mm	.590	15mm	1.063	27mm	50	500	786210-99922
CC-PG-12-G	1/2"	GRAY	.394-.591	10-14mm	.590	15mm	1.063	27mm	50	500	786210-99926
CC-PG-34-B	3/4"	BLACK	.511-.709	13-18mm	.590	15mm	1.299	33mm	25	100	786210-99923
CC-PG-34-G	3/4"	GRAY	.511-.709	13-18mm	.590	15mm	1.299	33mm	25	100	786210-99927
CC-PG-1-B	1"	BLACK	.709-.984	18-25mm	.709	18mm	1.654	42mm	20	100	786210-99924
CC-PG-1-G	1"	GRAY	.709-.984	18-25mm	.709	18mm	1.654	42mm	20	100	786210-99928

Locknuts also available for NPT threaded fittings. Consult Technical Services for availability.

Listed under UL file E13938, control #137B

Call our toll-free 24-hour Fax-On-Demand Service for technical documentation, brochures and product literature.
1-800-858-6022

Thomas & Betts Corporation
Electrical Components Division
8155 T&B Boulevard
Memphis, Tennessee 38125
800-888-0211, ext. 8324 (Technical Services)
In Canada, 450-347-5318



T&B® Fittings

T&B Catalog Number: CC-NPT-12-G-2
UPC Number: 78621091575
Description: 1/2" CABLE GLAND W/2HOLE GROMMET

Status: Active

Packaging

T&B Sold in UM:	EACH
T&B Weight per UOM:	2.5 lbs. per 100

General Information

Country of Origin:	TURKEY
Harmonized Code:	3926909980

Application Support

Sales Drawings:	wsd-000375
-----------------	------------

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

For further technical assistance, please contact us...

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com