

# M35/26.FF

ABB contact for United  
States of America



## General Information

<b>Extended Product Type:</b>	M35/26.FF
<b>Product ID:</b>	1SNA115140R2300
<b>EAN:</b>	3472591151404
<b>Catalog Description:</b>	M35/26.FF
<b>Long Description:</b>	M35/26.FF Power Terminal Blocks - Feed-through - Grey,25mm <sup>2</sup> RatedCrossSection, 26mm Spacing G32, TH 35-7.5, TH 35-15 Rail

## Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Power Terminal Blocks

## Additional Information

<b>Ambient Temperature:</b>	-5 ... +40 °C
<b>Color:</b>	Grey
<b>Connecting Capacity-Main Circuit:</b>	Stud / Rigid 1x 2.5 ... 50 mm <sup>2</sup> Stud / Flexible 1x 2.5 ... 25 mm <sup>2</sup>
<b>Connection Type:</b>	Stud
<b>Function:</b>	Feed-through
<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Insulation Material:</b>	Polyamide
<b>Mounting on DIN Rail:</b>	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
<b>Number of Levels:</b>	1
<b>Pollution Degree:</b>	3
<b>Product Main Type:</b>	M35/26.FF
<b>Product Name:</b>	Terminal block
<b>Rated Cross-Section:</b>	25 mm <sup>2</sup>
<b>Rated Current (I<sub>n</sub>):</b>	Main Circuit 101 A
<b>Rated Short-time Withstand Current (I<sub>cw</sub>):</b>	for 1.0s 8000 A
<b>Rated Voltage (U<sub>r</sub>):</b>	1000 V
<b>Spacing:</b>	26 mm
<b>Sub-Function 3:</b>	2 connections

## Certificates and Declarations (Document Number)

<b>CSA Certificate:</b>	TBD-from cat 2010
<b>cUL Certificate:</b>	1SND165000A0203
<b>Declaration of Conformity - CE:</b>	1SND225008C1006
<b>EAC Certificate:</b>	1SND161009A1100
<b>RoHS Information:</b>	1SND230022F0201

## Classifications

<b>ETIM 4.0:</b>	EC000897 - Feed-through terminal block
<b>ETIM 5.0:</b>	EC000897 - Feed-through terminal block

**Object Classification Code:** X

---

## Container Information

---

**Package Level 1 Units:** 10 piece  
**Package Level 1 Width:** 120 mm  
**Package Level 1 Height:** 57 mm  
**Package Level 1 Length:** 130 mm  
**Package Level 1 Gross Weight:** 0.64000 kg  
**Package Level 1 EAN:** 3472591151404  
**Package Level 2 Units:** 300 piece  
**Package Level 2 Width:** 300 mm  
**Package Level 2 Height:** 300 mm  
**Package Level 2 Length:** 500 mm  
**Package Level 2 Gross Weight:** 19.7 kg  
**Package Level 3 Units:** 7200 piece  
**Product Packing Type:** Box

---

## Dimensions

---

**Product Net Width:** 26.0 mm  
**Product Net Height:** 66.0 mm  
**Product Net Depth:** 44.0 mm  
**Product Net Weight:** 64.00 g

---

## Environmental

---

**Ambient Air Temperature:** Operation -55 ... +110 °C  
Storage -55 ... +110 °C  
**RoHS Status:** Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007-01-01

---

## Ordering

---

**EAN:** 3472591151404  
**Minimum Order Quantity:** 10 piece  
**Customs Tariff Number:** 85369010

---

## Technical UL/CSA

---

**Maximum Operating Voltage  
UL/CSA:** Main Circuit 600 V  
**Connecting Capacity-Main Circuit  
UL/CSA:** Stud / Rigid 1x 10 ... 2 AWG

---

